

**Mathis-Sieco Model RM-750
with Heavy Duty FESCO Hitch**

Fire Plow Suppression Complete With Following Specifications

DISC: 20" dia. X 1/4" Thick

COULTER BLADE: 20" dia. X 3/8" Thick

COULTER ARMS: Adjustable 1" Steel Flat Bar

SPREADER BAR: 4" Ship and Car Channel, 1/2" Thick

HYDRAULIC CYLINDER: 4" Bore, 2" Ram, 12" Stroke, Clevis Mount, Extended Ports, Welded Base

FRAME: Side Plates; 9" Wide, 7/8" Thick High Tensile Steel

PLOW SWIVEL: 2 3/16" dia. Vertical Pin, 1 1/2" Horizontal Pin, 1 1/4" dia. Cylinder Pins

PLOW FRAME HITCH: 1 1/2" dia. Horizontal Pin, 2-Position Adjustable

MOUNT BRACKET HITCH TRACTOR: 2 3/16" dia. Vertical Pin, All Welded Construction, Transport Locking Device, Can Be Operated from Tractor Seat

MIDDLEBUSTER HEEL: 1 1/4" Thick Steel with Bolt On 14" Middlebuster

SPRING ROD: 1 1/4" dia. With 1 1/4" dia. Horizontal Pin, Adjustable

SPRING: Compression Type, Right Hand Wound 2 3/4" o.d. X 18" Free Height X 19/32" dia. Alloy Steel

DISC BOXES: To Be Sandwich Mounted on Both Sides of Middlebuster Heel

DEPTH SLIDE: Adjustable

APPROACH ANGLE: 32 Degree Approximate

DISC HUB: Cast 10" Disc Hub Flange

Recommended HorsePower: 52 to 65 HP

Approximate Weight: 1325#

ALL SPECIFICATIONS SUBJECT TO CHANGE AND ARE FOR DESCRIPTIVE USE

052003