

SPECIFICATIONS
FESCO MODEL RM-1250 WITH H.D. FESCO HITCH

DISC BLADES: 28" DIA. X 3/8" THICK

COULTER BLADES: 24" DIA. X 3/8" THICK

SPREADER BAR: 7" SHIP AND CAR CHANNEL WITH 3 1/2" FLANGE

WINGS: MOULDBOARD TYPE 1/2" PLATE

HYDRAULIC CYLINDER: 4" BORE, 2" RAM, 12" STROKE, CLEVIS MOUNTED, EXTENDED PORTS, WELDED CONSTRUCTION

FRAME: SIDE PLATES 9" WIDE, 7/8" THICK HIGH TENSILE STEEL

PLOW SWIVEL: 2 3/16" DIA. VERTICAL PIN, 1 1/2" DIA. HORIZONTAL PIN, 1 1/4" DIA. CYLINDER PIN, T-1 STEEL CONSTRUCTION

PLOW FRAME HITCH & STABILIZER: 1 1/2" DIA. HORIZONTAL PIN, 2-POSITION ADJUSTABLE WITH ROCKING CHAIR TYPE STABILIZER WELDED TO PLOW FRAME HITCH

TRACTOR HITCH MOUNT BRACKET: 2 3/16" DIA. VERTICAL PIN ALL WELDED CONSTRUCTION WITH ROLLED RUB PLATE TO ALLOW ROCKING CHAIR TYPE STABILIZER TO BUMP AND STRAIGHTEN PLOW BEHIND TRACTOR AS PLOW LEAVES GROUND, THUS PREVENTING PLOW FROM SWINGING LEFT OR RIGHT WHILE BRINGING PLOW TO RAISED LOCKED POSITION. TRANSPORT LOCKING DEVICE CAN BE OPERATED FROM TRACTOR SEAT

MIDDLEBUSTER HEEL: 1 1/4" THICK BOLT ON MIDDLEBUSTER 18" WIDE

SPRING ROD: (2) 1 1/4" DIA. RODS WITH 1 1/4" DIA. HORIZONTAL PIN ADJUSTABLE

SPRING: (2) COMPRESSION TYPE, RIGHT HAND WOUND 2 3/4" O.D. X 18" FREE HEIGHT X 19/32" DIA. ALLOY STEEL

DISC BOXES: CAST HEAVY DUTY 4-BOLT MOUNTED ON BOTH SIDES OF FRAME AT 45 DEGREE ANGLE TO MAIN FRAME WITH 15 DEGREE ANGLE TILT BACK, TAPER ROLLER BEARING EQUIPPED WITH GREASE SEAL. INSIDE CUP 5.25 O.D., INSIDE BEARING BORE 3.25", OUTSIDE CUP 4.125" O.D., OUTSIDE BEARING BORE 2.250"

DISC HUB & SPINDLE: 2 PIECE, CAST STEEL FLANGE WITH ALLOY STEEL SPINDLE PRESSED AND WELDED

DEPTH SLIDE: ADJUSTABLE

RECOMMENDED HORSEPOWER: 85 TO 115 HP

APPROXIMATE WEIGHT: 1900#

ALL SPECIFICATIONS SUBJECT TO CHANGE AND ARE FOR DESCRIPTIVE USE
F.O.B. STARKVILLE, MISSISSIPPI 052003