

SPECIFICATIONS
FESCO MODEL RM-1500 WITH H.D. FESCO HITCH

DISC BLADES: 28" DIA. X 3/8" THICK

COULTER BLADES: 30" DIA. X 3/8" THICK

SPREADER BAR: 4"x4"x1/2" ANGLE REINFORCED AT ALL STRESS POINTS

WINGS: MOULDBOARD TYPE 1/2" PLATE

HYDRAULIC CYLINDER: 5" BORE x 16" STROKE x 2 1/2" DIA. RAM

FRAME: 4" X 12" X 1/2" RECT. TUBING 80" IN LENGTH

PLOW SWIVEL: FABRICATED 2 3/16" DIA. VERTICAL AND HORIZONTAL PIN, 1 1/4" DIA. CYLINDER PIN

PLOW FRAME HITCH & STABILIZER: 2 3/16" HORIZONTAL PIN, 10 BOLT 2-POSITION ADJUSTABLE

TRACTOR HITCH MOUNT BRACKET: 2 3/16" DIA. VERTICAL PIN ALL WELDED CONSTRUCTION WITH ROLLED RUB PLATE TO ALLOW ROCKING CHAIR TYPE STABILIZER TO BUMP AND STRAIGHTEN PLOW BEHIND TRACTOR AS PLOW LEAVES GROUND, THUS PREVENTING PLOW FROM SWINGING LEFT OR RIGHT WHILE BRINGING PLOW TO RAISED LOCKED POSITION. TRANSPORT LOCKING DEVICE CAN BE OPERATED FROM TRACTOR SEAT

MIDDLEBUSTER HEEL: 1 1/4" THICK BOLT ON 18" MIDDLEBUSTER

SPRING ROD: (2) 1 1/4" DIA. RODS WITH 1 1/4" DIA. HORIZONTAL PIN ADJUSTABLE

SPRING: (2) COMPRESSION TYPE, RIGHT HAND WOUND 2 3/4" O.D. X 18" FREE HEIGHT X 19/32" DIA. ALLOY STEEL

DISC BOXES: CAST HEAVY DUTY 4-BOLT MOUNTED ON BOTH SIDES OF FRAME AT 45 DEGREE ANGLE TO MAIN FRAME WITH 15 DEGREE ANGLE TILT BACK, TAPER ROLLER BEARING EQUIPPED WITH GREASE SEAL. INSIDE CUP 5.25 O.D., INSIDE BEARING BORE 3.25", OUTSIDE CUP 4.125" O.D., OUTSIDE BEARING BORE 2.250"

DISC HUB & SPINDLE: 2 PIECE, CAST STEEL FLANGE WITH ALLOY STEEL SPINDLE PRESSED AND WELDED

COULTER BOXES: DUCTILE CAST, TAPER ROLLER EQUIPPED WITH GREASE SEAL AND 4-BOLT CAP. EACH BOX BOLTED TO FRAME WITH (4) 5/8"x2 1/4" CAP SCREWS. INSIDE CUP 3.346" O.D., INSIDE BEARING BORE 1.750", OUTSIDE CUP 4.125" O.D., OUTSIDE BEARING BORE 2.250"

DEPTH SLIDE: ADJUSTABLE

RECOMMENDED HORSEPOWER: 105-200 HP
3150#

APPROXIMATE WEIGHT:

ALL SPECIFICATIONS SUBJECT TO CHANGE AND ARE FOR DESCRIPTIVE USE
F.O.B. STARKVILLE, MISSISSIPPI
052003